



## Walraven RapidStrut® Slide Nut G2 (BUP1000)

(H2404)

for quick connection of clamps and threaded rods



### Features & benefits

- slide nut with washer and Walraven RapidStrut® spring
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- Tested values in combination with Walraven RapidStrut® Rail 41x41x2.5mm, more details can be found on the Technical Datasheet.
- M10 and M12 are tested for fire safety according to EN 1366-1.

Product Number	Thread Size	Material Thickness	Maximum Allowed Load Fax	Maximum Allowed Load Faz	Total Width x Total Height x Total Depth
Reference letter	TS	MT	Fa,x	Fa,z	W x H x DtT
Unit description		(mm)	(N)	(N)	(mm) x (mm) x (mm)
665185106	M6	5	950	2660	43.22 x 24.29 x 40.80
665185108	M8	6	1100	3120	43.22 x 24.29 x 40.80
665185110	M10	8	1250	5000	43.22 x 24.29 x 40.80
665185112	M12	9	2440	5000	43.22 x 24.29 x 40.80