

## Walraven RapidStrut® Slide Nut (hdg)

(H2425)

to connect construction parts to the rail



### Features & benefits

- material: slide nut made of steel 1.0332
- hot dip galvanized
- M10 and higher are tested for fire safety
- Tested values in combination with Walraven RapidStrut® Rail 41x41x2.5mm.
- More details can be found on the Technical Datasheet.

Product Number	For Rail Type	Thread Size	Material Thickness	Torque Moment For Installation	Maximum Allowed Load Fax	Maximum Allowed Load Faz	Total Width x Total Height x Total Depth
<i>Reference letter</i>		<i>TS</i>	<i>MT</i>	<i>T inst.</i>	<i>Fa,x</i>	<i>Fa,z</i>	<i>W x H x DtT</i>
<i>Unit description</i>			<i>mm</i>	<i>Nm</i>	<i>N</i>	<i>N</i>	<i>mm x mm x mm</i>
6518006	41x21, 41x41, 41x51, 41x62, 41x82	M6	5	7	950	2,660	34 x 5 x 19
6518008	41x21, 41x41, 41x51, 41x62, 41x82	M8	6	25	2,200	4,500	34 x 6 x 19
6518010	41x21, 41x41, 41x51, 41x62, 41x82	M10	8	40	2,550	5,000	34 x 8 x 19
6518012	41x21, 41x41, 41x51, 41x62, 41x82	M12	9	50	2,950	5,000	34 x 9 x 19