


Walraven RapidStrut® Rail T-Connector G2 (BUP1000)

(H28109)



Features & benefits

- connector with pre-assembled Walraven RapidStrut® Slide nut(s)
- to make fabrication with Walraven RapidStrut® Rail
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- 'Direct Twist' technology for easy and secure installation
- visual guide to check the position of the slide nut
- optimized for easy installation with electrical tools
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227

Product Number	For Rail Type	Total Width x Total Height x Total Length	Material Thickness	Width	Torque Moment For Installation	Maximum Al- lowed Load Faz	Maximum Al- lowed Load Fax
Reference letter		$W \times H \times L$	MT	w	$T_{inst.}$	$F_{a,z}$	$F_{a,x}$
Unit description		$mm \times mm \times mm$	mm	mm	Nm	N	N
665885213	41x21, 41x41, 41x51, 41x62, 41x82	80 x 31.4 x 131	5	80	40	4,000	2,270