


Walraven RapidStrut® Connector 90° (BUP1000)

(H2813)



Features & benefits

- angle connector for all Walraven RapidStrut® rails to make fabrications
- the hole pattern is adapted to the hole pattern of Walraven RapidStrut® rails to use throughbolts
- user friendly by rounded edges
- with reinforced bend for extra strength
- material: steel 1.0242 (S250GD) + ZM310 MAC
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227



Product Number	For Rail Type	Angle	Total Width x Total Height x Total Length	Material Thickness	Width	Torque Moment For Installation
Reference letter		<i>a</i>	<i>W x H x L</i>	<i>MT</i>	<i>w</i>	<i>T_{inst.}</i>
Unit description		°	mm x mm x mm	mm	mm	Nm
66588201	41x21, 41x41, 41x51, 41x62, 41x82	90	40 x 62 x 62	4	40	30
66588207	41x21, 41x41, 41x51, 41x62, 41x82	90	40 x 62 x 42	4	40	30
66588221	41x21, 41x41, 41x51, 41x62, 41x82	90	40 x 110 x 62	4	40	30
66588228	41x21, 41x41, 41x51, 41x62, 41x82	90	40 x 110 x 110	4	40	30