

Walraven Yeti® 335 Frame Set


(I0415)

Set for quick installation of units on flat roofs



6768 5 501

6768 5 502



Features & benefits

- complete set for supporting installation appliances on flat roofs
- suitable for wide range of commonly used airco's, ventilation units, etc.
- with non-slip anti-vibration mat
- predefined load capacity: calculation not necessary
- device can't be heavier than 150 kg
- top of device can't be higher than 1.2 m over the roof level
- mouldings made of WPC, a composite of recycled plastic and wood fibre
- product is part of the Walraven Walraven UltraProtect® 1000 system
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3 up to 31 dB(A)
- sets meet the requirements of DIN 18531-1
- UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
- Before mounting, the roof load capacity has to be confirmed by a structural engineer.
- If changes to the mounting parameters is necessary then please contact Walraven Technical Department

Product Number	Total Width x Total Height x Total Length	Height	Height 2	Length	Width
Reference letter	W x H x L	h	h 2	l	w
Unit description	(mm) x (mm) x (mm)	(mm)	(mm)	(mm)	(mm)
67685501	1376 x 520 x 1876	520	20	1794	1295
67685502	1876 x 520 x 2376	520	20	2294	1000