
Walraven Yeti® 335 Frame Set 41|H (BUP1000)

(10424)

Set for quick installation of units on flat roofs





 $A \ge 200 (F_{max.} = 625 N)$ $A \ge 400 (F_{max.} = 750 N)$ $A \ge 600 (F_{max.} = 825 N)$











Features & benefits

- complete set for supporting installation appliances on flat roofs
- suitable for wide range of commonly used airco's, ventilation units, etc.
- with non-slip anti-vibration mat
- predefined load capacity: calculation not necessary
- mouldings made of WPC, a composite of recycled plastic and wood fibre
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3 up to 31 dB(A)
- sets meet the requirements of DIN 18531-1
- UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
- Before mounting, the roof load capacity has to be confirmed by a structural engineer.
- If changes to the mounting parameters is necessary then please contact Walraven Technical Department.
- The maximum recommended loads are calculated without accounting for wind and snow actions, which can vary significantly depending on local conditions. To ensure safety under typical circumstances, a global safety factor of 2 is applied.
- For project-specific calculations or site-specific conditions, please contact Walraven Technical Support for detailed assistance

Product Number	Total Width x Total Height x Total Length	Height	Length	Width
Reference letter	WxHxL	h	1	W
Unit description	mm x mm x mm	mm	mm	mm
67685500	1,377 x 520 x 1,494	500	1,200	1,000