walraven

(10424)

Walraven Yeti® 335 Frame Set (BUP1000)

Set for quick installation of units on flat roofs

			Fmax=490N	L Fmax=490N	Friax=750N	Fmax=7	eatures & ber complete set for on flat roofs suitable for wide ventilation units with non-slip ar predefined load device can't be h top of device ca roof level mouldings made plastic and woo product is part of
((•)) 50 10140-1	50 10140-3	B					UltraProtect® 10 stands min. 1,00 red rust) accord noise reduction and DIN EN ISO sets meet the re UV-resistance a 02 - certified by Before mounting confirmed by a s If changes to th necessary then p Department

tures & benefits

- complete set for supporting installation appliances on flat roofs
- suitable for wide range of commonly used airco's, ventilation units, etc.
- with non-slip anti-vibration mat
- predefined load capacity: calculation not necessary
- device can't be heavier than 150 kg
- top of device can't be higher than 1.2 m over the roof level
- mouldings made of WPC, a composite of recycled plastic and wood fibre
- product is part of the Walraven Walraven UltraProtect[®] 1000 system
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3 up to 31 dB(A)
- sets meet the requirements of DIN 18531-1
- UV-resistance according to EN ISO 16474-3:2014-02 - certified by ITB
- Before mounting, the roof load capacity has to be confirmed by a structural engineer.
- If changes to the mounting parameters is necessary then please contact Walraven Technical Department

Product Number	Total Width x Total Height x Total Length	Height	Height 2	Length	Width
Reference letter	WxHxL	h	h 2	1	W
Unit description	(mm) x (mm) x (mm)	(mm)	(mm)	(mm)	(mm)
67685500	1377 x 520 x 1494	520	20	1494	1377