

Walraven Chemical Anchor WVSF200

(L0390)

high performance chemical anchoring system for cracked concrete and rebar connections



Features & benefits

- reduced edge and anchor spacing distances
- always correct mixing ratio thanks to the static mixer nozzle
- approved for use with rebars as anchors in non-cracked concrete
- cartridge may be used up over several times (each installation after a break requires new mixing nozzle)
- ETA Option 1 approval for cracked and non-cracked concrete
- A+ VOC emissions class
- ETA TR023 for post-installed rebar connections
- seismic performance category C1 for design of anchorages under seismic action
- WRAS Material Approval for contact with potable water
- for loads and more information, refer to the product data sheet and/or the ETA reports
- substrate type: cracked concrete, non-cracked concrete

Product Number	Cartridge Volume	Processing Temperature	Curing Time	Amount of Nozzles	Total Width x Total Height x Total Depth
<i>Reference letter</i>					<i>W x H x Dt</i>
<i>Unit description (ml)</i>		<i>(°C)</i>	<i>(min)</i>		<i>(mm) x (mm) x (mm)</i>
6099123CZ	300	5 - 30	40 - 145	1	60 x 260 x 60
6099123E	300	5 - 30	40 - 145	1	60 x 260 x 60
6099126E	300	5 - 30	40 - 145	1	60 x 260 x 60