



Walraven TWIST

(L1020)

fixing to concrete, brick



Features & benefits

- plug anchors itself when tightening the screw
- does not rotate on screwing
- easy and quick to use
- for (middle)heavy fixings in solid or hollow materials
- pre-drill hole Ø 8 mm or 10 mm and insert plug
- stays in position, when screw is removed
- with collar to prevent plug from falling into hollow space
- suitable for metric thread and chipboard screws
- better fire resistance than plastic plugs
- HØ 10mm: torque is max. 7.5 Nm
- max. allowed load (Fa) in brick (safety margin 1:2)
- material: steel
- surface treatment: zinc plated, white passivated

Product Number	Total Length	Minimum Screw Depth	Drill Hole Diameter	Drill Hole Depth	Screw Size	Screw Length	Suitable For Screw Diameter	Total Height	Total Width
Reference letter	L	ls,min	d0	h0	ds	ls		H	W
Unit description	mm	mm	mm	mm		mm	mm	mm	mm
6119141	45	60	8	55	5	60	5	8	8
6119641	50	70	10	65	6	70	6	10	10
6119653	70	70	10	65	6	70	6	15	25
6119731	60	60	10	60	M6	60	6	15	25
6119753	60	60	10	60	M6	60	6	15	25