## walraven

	acifyre <sup>®</sup> Wool Coa	ting	(U2010)	
<image/>			<ul> <li>Coating or filler designed for fire protection in cables and penetration seals</li> <li>Particularly suitable for applications requiring thin dry film thicknesses</li> <li>Forms a ceramifying protective layer when exposed to fire due to the Strong Endothermic Reaction</li> <li>Suitable for protective cable coating, cable and pipe penetration sealing, and large-surface bonding on critical substrates</li> <li>Can be applied indoors and in sheltered outdoor areas</li> <li>Withstands humidity, freeze-thaw cycles, UV radiation, and various oils and chemicals</li> <li>Solvent-free and halogen-free</li> <li>Offers strong mechanical resistance</li> <li>Coating can be applied using a brush, paint roller, or airless spraying machine</li> <li>Provides protection up to El 120</li> <li>Tested and approved according to EN 1366-3</li> </ul>	
Product Number	Colour	Volume	Volume (kg)	Total Width x Total Height x Total Length
Reference letter				WxHxL
Unit description		(ml)	(kg)	(mm) x (mm) x (mm)
2139400001	White		12.50	264 x 218 x 344
2139400003	White	310		50 x 50 x 240

5

2139400005

White

227 x 180 x 227