

Walraven Yeti® 280


Technical Data Sheet

All internal tests were conducted using the Walraven RapidStrut® 41|H channel type. The test results were evaluated in accordance with the STEP method, as outlined in the RAL GZ-655:2008 guideline. The recommended load values presented in this data sheet are based on actual tests and are further supported by the manufacturer's extensive experience with previously installed projects.



67685281

Articlecode	Description	Total Width (mm)	Total Length (mm)	Total Height (mm)	Height 2 channel base (mm)	Effective area A_{eff} [m ²]	Weight [kg]
67685281	Walraven Yeti® 280	283,0	283,0	58,0	10,0	0,074	0,76



	Standing on concrete	Standing on styrodur 4000 CS, ds	Standing on EPS DAA dm
Characteristic resistance Rk [kN]	16,76	13,64	3,50
Recommended Load F [kN]	8,38	5,00	1,75

The recommended Load [kN] is calculated by applying a safety factor of 1.4 for static load considerations, 1.1 for potential material variations, and 1.3 for empirical data usage, resulting in a total factor of $\gamma=2.0$.

The recommended Load [kN] also considers the long-term maximum compression force permitted for the type of insulation, based on the manufacturer's technical data.

Sound reduction and UV-resistance impact



Sound & vibration proof

With non-slip anti-vibration mat.

Type of foot	Load per foot	Insulation type	Sound reduction acc. EN ISO 717-2
Walraven Yeti® 280	100 kg	without	$\Delta Lw = 19$ dB
Walraven Yeti® 280	100 kg	EPS DAA dm	$\Delta Lw = 27$ dB
Walraven Yeti® 280	200 kg	EPS DAA dm	$\Delta Lw = 28$ dB
Walraven Yeti® 280	300 kg	EPS DAA dm	$\Delta Lw = 29$ dB



Test procedure

EN ISO 16474-3:2014-02

method

A

cycle

1

conclusions

EN ISO 4628-1:2016-03

EN ISO 178:2011 + A1:2013-06

Sufficient resistance to UV exposure

For a detailed calculation, design and for support how to spread the load, please contact Walraven Technical Support.

Find out how we can support you

Would you like to find out more about any of the solutions described in this Technical Data Sheet?
Or would you like to discuss how we could help you find the best possible solution for your project?
Get in touch today!

Technical Data Sheet Walraven Yeti® 280 (EN-INT) – 09/2025 – PDF – Full content subject to modifications
* The technical data are non-binding and do not reflect the warranted characteristics of the products. They are subject to change. Please consult our General Terms and Conditions. Additional information is available upon request. It is the designer's responsibility to select products suitable for the intended purpose and to ensure that performance data are not exceeded. The installation instructions should always be read and followed.

Walraven International

Industrieweg 5
3641 RK Mijdrecht (NL)
Tel. +31 297 23 30 00
Fax +31 297 23 30 99
export@walraven.com

Walraven Group

Mijdrecht (NL) · Tienen (BE) · Bayreuth (DE) · Banbury (GB) · Malmö (SE) · Grenoble (FR) · Barcelona (ES)
Milan (IT) · Kraków (PL) · Mladá Boleslav (CZ) · Kyiv (UA) · Danville (US) · Dubai (AE) · Budapest (HU) · Mumbai (IN)
Singapore (SG) · Burlington (CA)